

Graphene inks



Additive-free graphene inks for printed electronics (2D) and structural elements (3D)

- **highly concentrated for efficient printing**
- **rheology adjustable to all major printing and coating techniques, no need for post-treatment**
- **up-scalable and versatile technology, large choice of solvents, substrates, and 2D materials**

Invention

A simple and efficient preparation process for inks with a high solid content of 2D materials has been developed. The method can be used for pristine 2D materials of virtually all types, to prepare additive-free inks with diverse rheological properties for various printing and coating methods. Depending on the selected 2D material, thin and thick, conductive, semiconductive (with different bandgaps), or insulating films can be deposited on almost all substrates, using freely selectable solvents, while no post-treatment (e.g., sintering or high-temperature thermal treatments) is required.

Background

Printing and wet coating methods are widely used for commercial production of electronics. Usually conventional inks contain enormous amounts of additives such as binders and surfactant, which drastically degrade the electronic properties of the functional materials. To remove the additives and recover the electronic properties, high-temperature post-treatments ($>300^{\circ}\text{C}$) are required, limiting the choice of materials (e.g., no heat-sensitive material). Furthermore, conventional 2D material inks (e.g., graphene inks) are usually produced using hazardous solvents (e.g., NMP) and have low solid contents that complicates the fabrication process and increases the production cost and time.

In this regard, the new high-solid-content, additive-free inks produced in green solvents without the need for additional post-treatment (except for drying) can offer a vast range of possibilities for functional printing/coating and are highly desirable for commercial production of electronics.

Advantages

These new inks are based on a high concentration of pristine 2D materials (e.g., graphene, 2D single element materials, 2D alloys, 2D supercrystals), in which – contrarily to diluted dispersion – a solvent is dispersed in the solid without the need for additives. These inks show high colloidal stability, exhibit exceptional adhesion to a wide range of substrates, and are producible using almost any solvent (including green solvents). These inks can be optimized for all common printing techniques as rheological properties can be easily adjusted over a wide range. Graphene inks are significantly cheaper than metallic inks (e.g., silver or copper) and are chemically inert/stable. Since no heat treatment is needed to achieve full functionality, printing and coating on heat-sensitive substrates (e.g., Paper, PET, PLA, etc.) or layers (e.g., perovskites) are possible. Being additive-free, our printed/coated films are highly porous (porosity level is adjustable), which is desirable for sensing and energy storage applications, new possibilities may arise by functionalizing the inks with biomolecules.

Applications

The inks can be applied in all fields of printed electronics where conductive, semiconductive or isolating features with low temperature processing is needed or desired. Specific applications may be

1. Energy storage and conversion (e.g., batteries, supercapacitors, solar cells, fuel cells, etc.);
2. Sensors (e.g., chemical, temperature, pressure, etc.);
3. Electromagnetic interface (EMI) shielding;
4. Thermal interface material (both in solid and gel form).



The inks are specifically suited for extrusion- and screen-printing. Further applications are in the field of stretchable wires and interconnects, embedded electronics, self-healing circuits, conformal electrodes, heat transfer systems, and thermal cooling and heating designs.

Ownership

Empa, Swiss Federal Laboratories for Materials Testing and Research, Überlandstrasse 129, CH-8600 Dübendorf; Patent pending

References

A Universal Approach for Room-temperature Printing and Coating of Two-dimensional Materials, Advanced Materials 2021, <https://doi.org/10.1002/adma.202103660>
Homogeneous emulsions and suspensions of 2-dimensional materials, Patent application EP3848420A1

Keywords

2D materials, Printing and Coating, Printed electronics, Flexible electronics, Room-temperature processing

Contact

Empa, Technology Transfer
Dr Andreas Kündig, andreas.kuendig@empa.ch
Phone +41 58 765 48 30

Technical Information

Dr Jakob Heier, jakob.heier@empa.ch
Phone +41 58 765 43 45

Dr Sina Abdolhosseinzadeh, sina.abdolhosseinzadeh@empa.ch
Phone +41 58 765 66 50



Empa

Materials Science and Technology

Empa

CH-8600 Dübendorf
Überlandstrasse 129

Telefon +41 58 765 11 11
Telefax +41 58 765 11 22

CH-9014 St. Gallen
Lerchenfeldstrasse 5

Telefon +41 58 765 74 74
Telefax +41 58 765 74 99

CH-3602 Thun
Feuerwerkerstrasse 39

Telefon +41 58 765 11 33
Telefax +41 58 765 69 90

www.empa.ch

Empa is an interdisciplinary research and service institution within the ETH Domain covering selected fields of materials science and technology development including important environmental issues. Empa's R&D activities focus on the requirements of industry and the needs of society, thus linking research to engineering, and science to industry and society. As a result, Empa is capable of providing its partners with customized services and solutions that not only enhance their innovative edge, but also help to improve the quality of life for the public at large. Safety, reliability and sustainability of materials and systems are cross-sectional topics and a hallmark of all Empa activities. As such, Empa plays a key role in Switzerland's research and innovation landscape.